

Dimensions - ParkBoard PQi - US West

Dimensions shown do not include optional additional space to compensate for column width
Please consult with your Klaus representative for assistance with layout

ParkBoardPQi Length Selector (These are layout examples. Actual stalls can be any length)

Design Notes

- 1) These configurations are examples. Actual lengths can be anything over 15 feet. Check building codes for your jurisdiction.
- 2) Longer stalls are recommended to allow for easier parking and to accommodate the largest mix of vehicles.

	Extended Length			Extra Length			Standard Length			Reduced Length		
	ft - in	inches	(cm)	ft - in	inches	(cm)	ft - in	inches	(cm)	ft - in	inches	(cm)
Stall Length	18' - 9"	225"	(570)	18' - 5"	221"	(560)	18' - 1"	217"	(550)	17' - 9"	213"	(540)
Max Vehicle Length	18' - 1"	217"	(550)	17' - 9"	213"	(540)	17' - 5"	209"	(530)	17' - 1"	205"	(520)
Pallet Length	12' - 0"	144"	(366)	12' - 0"	144"	(366)	12' - 0"	144"	(366)	12' - 0"	144"	(366)
Length per Row	18' - 9"	225"	(570)	18' - 5"	221"	(560)	18' - 1"	217"	(550)	17' - 9"	213"	(540)
Length Required 2-Row	37' - 5"	449"	(1140)	36' - 9"	441"	(1120)	36' - 2"	434"	(1100)	35' - 6"	426"	(1080)
Length Required 3-Row	56' - 2"	674"	(1710)	55' - 2"	662"	(1680)	54' - 2"	650"	(1650)	53' - 2"	638"	(1620)

ParkBoardPQi Width Selector

Design Notes

- 1) Choose the stall width from the top.
 - Model -240 or wider is recommended for 2 row systems. Model -250 or wider is recommended for 3-Row systems.
 - Wider stalls are recommended when EV charging will be used.
- 2) Choose the number of grids from the left column
- 3) Find the system width from the table
 - Dimensions are minimum. Additional spacing can be added to accommodate columns etc.

Platform Model 6100/6200/6300	-260 (ExtraWide)			-250 (Wide)			-240 (Standard)			-230 (Narrow)		
	ft - in	in	(cm)	ft - in	in	(cm)	ft - in	in	(cm)	ft - in	in	(cm)
Platform Width (RB)	9' 5:3/8"	114"	(288)	9' 1:1/2"	110"	(278)	8' 9:1/2"	106"	(268)	8' 5:5/8"	102"	(258)
Tread width	8' 6:3/8"	103"	(260)	8' 2:3/8"	99"	(250)	7' 10:1/2"	95"	(240)	7' 6:1/2"	91"	(230)
System Total Width Wall-to-Wall (T)												
2-wide	19' - 7"	235"	(596)	18' - 11"	227"	(576)	18' - 3"	219"	(556)	17' - 8"	212"	(536)
3-wide	29' - 1"	349"	(884)	28' - 1"	337"	(854)	27' - 1"	325"	(824)	26' - 1"	313"	(794)
4-wide	38' - 6"	462"	(1172)	37' - 2"	446"	(1132)	35' - 10"	430"	(1092)	34' - 7"	415"	(1052)
5-wide	47' - 11"	575"	(1460)	46' - 4"	556"	(1410)	44' - 8"	536"	(1360)	43' - 0"	516"	(1310)
6-wide	57' - 5"	689"	(1748)	55' - 5"	665"	(1688)	53' - 5"	641"	(1628)	51' - 6"	618"	(1568)
7-wide	66' - 10"	802"	(2036)	64' - 7"	775"	(1966)	62' - 3"	747"	(1896)	59' - 11"	719"	(1826)
8-wide	76' - 3"	915"	(2324)	73' - 8"	884"	(2244)	71' - 0"	852"	(2164)	68' - 5"	821"	(2084)
9-wide	85' - 9"	1029"	(2612)	82' - 9"	993"	(2522)	79' - 10"	958"	(2432)	76' - 11"	923"	(2342)
10-wide	95' - 2"	1142"	(2900)	91' - 11"	1103"	(2800)	88' - 7"	1063"	(2700)	85' - 4"	1024"	(2600)
11-wide	104' - 8"	1256"	(3188)	101' - 0"	1212"	(3078)	97' - 5"	1169"	(2968)	93' - 10"	1126"	(2858)
12-wide	114' - 1"	1369"	(3476)	110' - 2"	1322"	(3356)	106' - 3"	1275"	(3236)	102' - 3"	1227"	(3116)
13-wide	123' - 6"	1482"	(3764)	119' - 3"	1431"	(3634)	115' - 0"	1380"	(3504)	110' - 9"	1329"	(3374)
14-wide	133' - 0"	1596"	(4052)	128' - 5"	1541"	(3912)	123' - 10"	1486"	(3772)	119' - 2"	1430"	(3632)
15-wide	142' - 5"	1709"	(4340)	137' - 6"	1650"	(4190)	132' - 7"	1591"	(4040)	127' - 8"	1532"	(3890)